

<b>BOWYER =</b>	C. Grozer	
<b>MODEL =</b>	<b>New Laminated TRH Manchurian Bow 2016</b>	
<b>BOW LENGTH =</b>	60	INCHES
<b>STRING LENGTH =</b>	58	INCHES (actual)
<b>STRING TYPE =</b>	B 50	ENDLESS
<b>STRING STRANDS</b>	16	
<b>BRACE HEIGHT =</b>	7,00	INCHES
<b>DRAW LENGTH =</b>	32	INCHES
<b>ARROW WEIGHT =</b>		GRAINS
<b>ARROW SPEED AVE =</b>		FPS

DR LNGTH (INCHES)	R FORCI (LBS)	CHANGE PER INCH
0,00		0,00
1,00		0,00
2,00		0,00
3,00		0,00
4,00		0,00
5,00		0,00
6,00		0,00
7,00		0,00
8,00		0,00
9,00	6,30	6,30
10,00	10,45	4,15
11,00	13,73	3,28
12,00	16,80	3,07
13,00	20,56	3,76
14,00	23,50	2,94
15,00	26,90	3,40
16,00	29,26	2,36
17,00	30,70	1,44
18,00	31,57	0,87
19,00	32,69	1,12
20,00	33,99	1,30
21,00	35,20	1,21
22,00	36,40	1,20
23,00	37,70	1,30
24,00	39,46	1,76
25,00	40,50	1,04
26,00	42,17	1,67
27,00	43,30	1,13
28,00	44,70	1,40
29,00	47,30	2,60
30,00	48,70	1,40
31,00	50,80	2,10
32,00	52,80	2,00

  

<b>PEAK DRAW FORCE (P.D.F.) =</b>	52,80	LB
<b>STORED ENERGY (S.E.) =</b>	66,29	FT.LB
<b>S.E./P.D.F. =</b>	1,255	FT.LB/LB
<b>ARROW K.E. =</b>	0,00	FT.LB
<b>DYNAMIC EFFICIENCY =</b>	0,00	%

